

J-LB LOOPBACK PATCHCORDS

Features:

- Compact design
- Easy installation
- Environmentally stable

Applications:

- Equipment interconnection
- Loopback for network
- Components testing



Performance Specifications:

ITEM			
Mode Type	Singlemode	Multimode	
Model	Uniboot LC SC SC/APC	MPO	Uniboot LC SC
Typical Insertion Loss, dB	0.3	1.0	0.3
Maximum Insertion Loss, dB	0.5	1.5	0.5
Operating Temperature, °C	-20~+70		

LOOPBACK PATCHCORDS

Ordering Information:

J - LB - □□ - □□

Connector Type

- AS SC/APC type
- SC SC type
- LC LC type
- MP MPO type
- XX Others, please specify

Fiber Type

- A Standard singlemode fiber
- C 50/125μm fiber
- D 62.5/125μm fiber
- F 50/125μm OM2
- K 62.5/125μm OM2
- G OM3
- X Others, please specify

Cable Type

- T Simplex, PVC tight buffer cable (0.9mm)
- H Simplex, Hytrel tight buffer cable (0.9mm)
- O Simplex, PVC cable (2.0mm)
- Q Simplex, PVC cable (3.0mm)
- B Simplex, LSZH semi-tight buffer cable (0.9mm)
- F Simplex, LSZH cable (2.0mm)
- I Simplex, LSZH cable (3.0mm)
- X Others, please specify